# POWER GENERATION G-Drive N45

# **SPECIFICATIONS**

Certification			Stage III A
No. of cylinders			4L
Injection System			M
Air Intake			TC
Displacement	liters		4.5
Exhaust System			I-EGR
Stand-by Power @ 1500 rpm		kWm	60
Prime Power @ 1500 rpm		kWm	55
Stand-by Power @ 1800 rpm		kWm	-
Prime Power @ 1800 rpm		kWm	-
Code			

### **WEIGHT AND DIMENSIONS**

Dimensions (L x W x H)	mm	1240 x 657 x 1061
Dry Weight	Kg	-

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

## Do you want to know more?

### LEGEND

Arrangemen	t
------------	---

L (in line)

V (90° "V" configuration)

### Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

# Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



